

SAFETY DATA SHEET

in accordance with 1907/2006/EC (REACH, as amended by 2015/830/EU) 29 CFR 1910.1200 and WHMIS 2015

Revision date: 26 April 2018 **Initial date of issue:** 12 July 2007 **SDS No.** 277-12a

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

ARC 5ES

1.2. Relevant identified uses of the substance or mixture and uses advised against

ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces. The product is used as a fast cure patching material that applies like putty.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel. +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
SDS requests: www.chesterton.com
E-mail (SDS questions): ProductMSDSs@chesterton.com
E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
Unit 105, Burlington, Ontario L7L 4X8 - Tel. 905-335-5055
EU: Chesterton International GmbH, Am Lenzenfleck 23,
D85737 Ismaning, Germany – Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)
NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS

Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
Aquatic Chronic 3, H412

2.1.2. Classification according to WHMIS 1988

D2A: Very toxic materials causing other effects; D2B: Toxic materials causing other effects

2.1.3. Australian statement of hazardous nature

Hazardous according to criteria of Safe Work Australia.

2.1.4. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16. The final cured material is considered nonhazardous.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS

Hazard pictograms:



Signal word:

Warning

Hazard statements:	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements:	P264	Wash hands thoroughly after handling.
	P272	Contaminated work clothing must not be allowed out of the workplace.
	P273	Avoid release to the environment.
	P280	Wear protective gloves and eye/face protection.
	P302/352	IF ON SKIN: Wash with plenty of soap and water.
	P362/364	Take off contaminated clothing and wash it before reuse.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337/313	If eye irritation persists: Get medical advice/attention.
	P501	Dispose of contents/container to an approved waste disposal plant.

Supplemental information: None

2.3. Other hazards

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Epoxy resin (number average molecular weight <= 700)	10-< 25	25068-38-6 500-033-5	NA	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
Other ingredients: Talc (non-asbestiform)	30-60	14807-96-6 238-877-9	NA	Not classified*
Silica (Quartz)	0.1-1	14808-60-7 238-878-4	NA	Not classified*
Carbon black	< 1	1333-86-4 215-609-9	NA	Not classified*

*Substance with a workplace exposure limit.
For full text of H-statements: see SECTION 16.

¹ Classified according to: * 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L.O. 111F), California Proposition 65
* 1272/2008/EC, GHS, REACH
* WHMIS 2015
* Safe Work Australia

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation:	Not applicable
Skin contact:	Remove contaminated clothing. Wash clothing before reuse. Wash skin with soap and water. Consult physician.
Eye contact:	Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.
Ingestion:	Do not induce vomiting. If person is conscious, rinse mouth with water and give small quantities of water to drink. Contact physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May cause skin sensitization as evidenced by rashes or hives.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water fog

Unsuitable extinguishing media: None known

5.2. Special hazards arising from the substance or mixture

Thermal decomposition may produce Carbon Monoxide, Carbon Dioxide, oxides of Sulfur and other toxic fumes.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code: 2 Z

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Scoop up and transfer to a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Avoid eye contact and excessive skin contact. Wash with soap and water immediately after use. Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated leather including shoes cannot be decontaminated and should be discarded. Utilize exposure controls and personal protection as specified in Section 8. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Epoxy resin (number average molecular weight <= 700)	–	–	–	–	–	–	–	–
Talc	20 mppcf	–	(resp)	2	(resp)	1	(resp)	2.5
Silica (Quartz) non-respirable	(resp)	0.05	(resp)	0.025	(resp)	0.1	(resp)	0.1
Carbon black	–	3.5	–	3	–	3.5	–	3

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]

Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:

Not available

Workers**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:**

Not available

8.2. Exposure controls**8.2.1. Engineering measures**

No special requirements. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed.

Protective gloves: Chemical resistant gloves (e.g., neoprene)

Eye and face protection: Safety glasses

Other: None

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	putty	Odour	sweet and amine odor
Colour	gray and black	Odour threshold	not determined
Initial boiling point	not applicable	Vapour pressure @ 20°C	0
Melting point	not determined	% Aromatics by weight	0
% Volatile (by volume)	< 1	pH	not applicable
Flash point	None	Relative density	2.247 kg/l
Method	PM Closed Cup	Weight per volume	18.75 lbs/gal.
Viscosity	> 10 million cps @25°C	Coefficient (water/oil)	< 1
Autoignition temperature	not determined	Vapour density (air=1)	> 1
Decomposition temperature	> 200°C (> 392°F)	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	not determined	Solubility in water	insoluble
Flammability (solid, gas)	not applicable	Oxidising properties	not applicable
Explosive properties	not applicable		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

No specific data.

10.5. Incompatible materials

No specific data.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Skin and eye contact. Personnel with pre-existing skin and eye disorders and skin allergies may be aggravated by exposure.

Acute toxicity -**Oral:**

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	LD50, rat	> 5000 mg/kg

Dermal:

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	LD50, rabbit	> 6000 mg/kg

Inhalation:

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	LC50, rat, 5 h	No mortality at vapor saturation level

Skin corrosion/irritation: Irritating to skin.

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	Skin irritation, rabbit	Moderate irritation / Severe irritation

Serious eye damage/irritation:

Irritating to eyes.

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	Eye irritation, rabbit	Mild irritation / Moderate irritation

Respiratory or skin sensitisation:

May cause skin sensitization as evidenced by rashes or hives.

Substance	Test	Result
Epoxy resin (number average molecular weight \leq 700)	Skin sensitization, guinea pig	Sensitizing

Germ cell mutagenicity:

Epoxy resin (number average molecular weight \leq 700): based on available data, the classification criteria are not met.

Carcinogenicity:

The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have classified inhaled silica as a human carcinogen. IARC has designated carbon black as possibly carcinogenic to humans (group 2B). The silica and carbon black in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin (number average molecular weight \leq 700): based on available data, the classification criteria are not met.

Reproductive toxicity:

Epoxy resin (number average molecular weight \leq 700): based on available data, the classification criteria are not met.

STOT-single exposure:

Not expected to cause toxicity.

STOT-repeated exposure:

Repeated or prolonged inhalation of Talc dust may cause chronic cough, shortness of breath, scarring of the lungs (pulmonary fibrosis) and mild symptomatic pneumoconiosis. Repeated inhalation of respirable free silica may cause scarring of the lungs with cough and shortness of breath. Silicosis, a delayed lung injury that is a disabling, progressive and sometimes fatal pulmonary fibrosis, may result. The silica and talc in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin (number average molecular weight \leq 700): not expected to cause toxicity.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information:

None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Epoxy resin: not readily biodegradable (OECD 301F, 28 days = 5%).

12.3. Bioaccumulative potential

Epoxy resin: low potential for bioaccumulation. (log Kow = 2.64 – 3.78, BCF = 31).

12.4. Mobility in soil

Putty. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Epoxy resin: if product enters soil, it will be mobile and may contaminate groundwater.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Unreacted components are a special waste (classified as hazardous according to 2008/98/EC). Combine resin and curative. The final cured material is considered nonhazardous. Landfill sealed containers with a properly licensed facility. May be incinerated at an appropriate facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

14.2. UN proper shipping name

ADR/RID/ADN/IMDG/ICAO: NON-HAZARDOUS, NON REGULATED

TDG: NON-HAZARDOUS, NON REGULATED

US DOT: NON-HAZARDOUS, NON REGULATED

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO: NOT APPLICABLE

TDG: NOT APPLICABLE

US DOT: NOT APPLICABLE

14.5. Environmental hazards

NOT APPLICABLE

14.6. Special precautions for user

NOT APPLICABLE

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

NOT APPLICABLE

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 94/33/EC on the protection of young people at work.

15.1.2. National regulations

US EPA SARA TITLE III

312 Hazards:

Immediate

313 Chemicals:

None

Other national regulations: National implementation of the EC Directive referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE: Acute Toxicity Estimate
BCF: Bioconcentration Factor
cATpE: Converted Acute Toxicity point Estimate
CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
ES: Exposure Standard
GHS: Globally Harmonized System
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
LC50: Lethal Concentration to 50 % of a test population
LD50: Lethal Dose to 50% of a test population
LOEL: Lowest Observed Effect Level
N/A: Not Applicable
NA: Not Available
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OECD: Organization for Economic Co-operation and Development
PBT: Persistent, Bioaccumulative and Toxic substance
(Q)SAR: Quantitative Structure-Activity Relationship
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
REL: Recommended Exposure Limit
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
STOT RE: Specific Target Organ Toxicity, Repeated Exposure
STOT SE: Specific Target Organ Toxicity, Single Exposure
TDG: Transportation of Dangerous Goods (Canada)
TWA: Time Weighted Average
US DOT: United States Department of Transportation
vPvB: very Persistent and very Bioaccumulative substance
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System
Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
Chemical Classification and Information Database (CCID)
European Chemicals Agency (ECHA) - Information on Chemicals
Hazardous Chemical Information System (HCIS)
National Institute of Technology and Evaluation (NITE)
Swedish Chemicals Agency (KEMI)
U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:

Classification	Classification procedure
Eye Irrit. 2, H319	Calculation method
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1, H317	Bridging principle "Dilution"
Aquatic Chronic 3, H412	Calculation method

Relevant H-statements: H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Exclamation mark

Changes to the SDS in this revision: Section 1.3.

Date of last revision: 26 April 2018

Further information: None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.