

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC 797(E) Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. Repair damage caused by impact, abrasion or erosion and chemical attack.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 2 of 15

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Special labelling of certain mixtures

EUH205	Contains epoxy constituents. May produce an allergic reaction.
--------	--

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	50-<75 %
	500-033-5	603-074-00-8
	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	10-<25 %
	500-006-8	01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs	5-<10 %
	271-846-8	603-103-00-4
	01-2119485289-22	
	Skin Irrit. 2, Skin Sens. 1; H315 H317	
100-51-6	benzyl alcohol	5-<10 %
	202-859-9	603-057-00-5
	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4; H332 H302	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 3 of 15

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 4 of 15

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.
Provide adequate ventilation.
Personal protection equipment: see section 8
Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8. Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapours/spray.
When using do not eat, drink or smoke.
Never use pressure to empty container. Keep/Store only in original container.
Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on handling

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area.
Street clothing should be stored separately from work clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container. Protect against direct sunlight.

Further information on storage conditions

Keep away from:
Frost
Heat
Humidity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 5 of 15

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 6 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			
Worker DNEL, long-term		inhalation	systemic	12,25 mg/m ³
Worker DNEL, acute		inhalation	systemic	12,25 mg/m ³
Worker DNEL, long-term		dermal	systemic	8,33 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	8,33 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	3,571 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	3,571 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,75 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,75 mg/kg bw/day
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, acute		dermal	local	0,0083 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs			
Worker DNEL, long-term		inhalation	systemic	3,6 mg/m ³
Worker DNEL, long-term		dermal	systemic	1 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day
100-51-6	benzyl alcohol			
Worker DNEL, long-term		inhalation	systemic	22 mg/m ³
Worker DNEL, acute		inhalation	systemic	110 mg/m ³
Worker DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,4 mg/m ³
Consumer DNEL, acute		inhalation	systemic	27 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 7 of 15

Consumer DNEL, long-term	dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	20 mg/kg bw/day

PNEC values

CAS No	Substance	Value
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	
	Freshwater	0,006 mg/l
	Marine water	0,001 mg/l
	Freshwater sediment	0,996 mg/kg
	Marine sediment	0,1 mg/kg
	Secondary poisoning	11 mg/kg
	Soil	0,196 mg/kg
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
	Freshwater	0,003 mg/l
	Freshwater sediment	0,294 mg/kg
	Marine sediment	0,029 mg/kg
	Soil	0,237 mg/kg
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs	
	Freshwater	0,007 mg/l
	Marine water	0,001 mg/l
	Freshwater sediment	307,16 mg/kg
	Marine sediment	30,72 mg/kg
	Soil	61,42 mg/kg
100-51-6	benzyl alcohol	
	Freshwater	1 mg/l
	Marine water	0,1 mg/l
	Freshwater sediment	5,27 mg/kg
	Marine sediment	0,527 mg/kg
	Micro-organisms in sewage treatment plants (STP)	39 mg/l
	Soil	0,456 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 8 of 15

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Use protective skin cream before handling the product.

Eye/face protection

Suitable eye protection:

Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: DIN EN 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material $\geq 0,4$ mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	transparent	
Odour:	characteristic	
pH-Value:		not determined

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	>95 °C

Flammability

Solid:	not determined
Gas:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 9 of 15

Explosive properties

No information available.

Lower explosion limits:

not applicable

Upper explosion limits:

not applicable

Ignition temperature:

not determined

Auto-ignition temperature

Solid:

not determined

Gas:

not determined

Decomposition temperature:

not determined

Oxidizing properties

No information available.

Vapour pressure:

not determined

Density (at 23 °C):

~1,13 g/cm³

Water solubility:

Immiscible

Solubility in other solvents

No information available.

Partition coefficient:

not determined

Viscosity / dynamic:
(at 23 °C)

~ 750 mPa·s

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Does not decompose when used for intended uses. No known hazardous decomposition products.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

- Amines
- Acid
- Alkali (lye)

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 10 of 15

10.6. Hazardous decomposition products

Gases/vapours, irritant

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 420
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
100-51-6	benzyl alcohol				
	oral	LD50 1620 mg/kg	Rat		
	inhalative vapour	ATE 11 mg/l			
	inhalative (4 h) aerosol	LC50 >4178 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin); Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; Oxirane, mono[(C12-14-alkyloxy)methyl] derivs)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 11 of 15

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)					
	Acute fish toxicity	LC50 3,6 mg/l	96 h	Oncorhynchus mykiss	Study report (1982)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2007)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1,7 mg/l	48 h	Daphnia magna	Study report (1984)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,3 mg/l	21 d	Daphnia magna	Study report (1984)	OECD Guideline 211
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1,8 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1993)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,3 mg/l	21 d	Daphnia magna	Study report (1984)	OECD Guideline 211
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 460 mg/l	96 h			
	Acute algae toxicity	ErC50 770 mg/l	72 h			
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna (Big water flea)		
	Algae toxicity	NOEC 51 mg/l	3 d			
	Crustacea toxicity	NOEC 310 mg/l	21 d			

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-51-6	benzyl alcohol			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	95 - 97%	21	

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	>= 2,64
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2,7
100-51-6	benzyl alcohol	1,1

BCF

CAS No	Chemical name	BCF	Species	Source
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	31		Study report (2010)
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	150		Other company data (
100-51-6	benzyl alcohol	1		

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 13 of 15

Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Classification code: M6
 Special Provisions: 274 335 375 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Marine pollutant: P
 Special Provisions: 274, 335, 969
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: A97 A158 A197
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 14 of 15

IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes
Danger releasing substance: epoxy resin

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs
benzyl alcohol

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EC50: Effectice concentration, 50 percent
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part A

Revision date: 12.10.2017

Page 15 of 15

vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself.
No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.
The user must make their own determination as to suitability.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)