

according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC S2(E) Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Chesterton International GmbH

Street: Am Lenzenfleck 23

Place: DE-85737 Ismaning GERMANY

Telephone: +49 89 99 65 46 - 0 Telefax: +49 89 99 65 46 - 50

e-mail: eu-sds@chesterton.com
e-mail (Contact person): eu-sds@chesterton.com
Internet: www.chesterton.com
Responsible Department: eu-sds@chesterton.com

1.4. Emergency telephone +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 2 of 14

Signal word: Warning

Pictograms:





Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulati	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
25068-38-6	2-(chloromethyl)oxirane;4-[2-(4-hyd	roxyphenyl)propan-2-yl]phenol		35-40 %	
	500-033-5	603-074-00-8	01-2119456619-26		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1, Aquatic Chronic 2; H315 H319 H3	17 H411		
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			15-20 %	
	500-006-8		01-2119454392-40		
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 3 of 14

(show directions for use or safety data sheet if possible).

After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately. Do not wash with: Solvents/Thinner

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

Provide adequate ventilation.

Personal protection equipment: see section 8

Remove persons to safety.



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 4 of 14

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a cool dry place. Keep container tightly closed.

Keep/Store only in original container.

Protect against direct sunlight.

Protect against: Frost

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
409-21-2	Silicon carbide (not whiskers), total inhalable	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, total inhalable	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

Print date: 12.01.2018



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 5 of 14

DNEL/DMEL values

CAS No	Substance				
DNEL type	·	Exposure route	Effect	Value	
25068-38-6	2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-	yl]phenol			
Worker DNEL	, long-term	inhalation	systemic	12,25 mg/m³	
Worker DNEL, acute		inhalation	systemic	12,25 mg/m³	
Worker DNEL	, long-term	dermal	systemic	8,33 mg/kg bw/day	
Worker DNEL	, acute	dermal	systemic	8,33 mg/kg bw/day	
Consumer DN	EL, long-term	dermal	systemic	3,571 mg/kg bw/day	
Consumer DN	EL, acute	dermal	systemic	3,571 mg/kg bw/day	
Consumer DN	EL, long-term	oral	systemic	0,75 mg/kg bw/day	
Consumer DN	EL, acute	oral	systemic	0,75 mg/kg bw/day	
1					
409-21-2	Silicon carbide				
Worker DNEL, acute		inhalation	systemic	94 mg/m³	
Consumer DN	EL, acute	inhalation	systemic	23 mg/m³	
Consumer DN	EL, acute	dermal	systemic	200 mg/kg bw/day	
Consumer DN	EL, acute	oral	systemic	13 mg/kg bw/day	
,					
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro	-2,3-epoxypropane an	d phenol		
Worker DNEL	, long-term	inhalation	systemic	29,39 mg/m³	
Worker DNEL	, long-term	dermal	systemic	104,15 mg/kg bw/day	
Worker DNEL	, acute	dermal	local	0,0083 mg/cm ²	
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m³	
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day	
13463-67-7	Titanium dioxide				
Worker DNEL	, long-term	inhalation	local	10 mg/m³	
Consumer DN	EL, long-term	oral	systemic	700 mg/kg bw/day	



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 6 of 14

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
25068-38-6	2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol	
Freshwater		0,006 mg/l
Marine water		0,001 mg/l
Freshwater s	ediment	0,996 mg/kg
Marine sedim	nent	0,1 mg/kg
Secondary po	pisoning	11 mg/kg
Soil		0,196 mg/kg
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	
Freshwater		0,003 mg/l
Freshwater s	ediment	0,294 mg/kg
Marine sedim	nent	0,029 mg/kg
Soil		0,237 mg/kg
13463-67-7	Titanium dioxide	
Freshwater		0,184 mg/l
Freshwater (i	ntermittent releases)	0,193 mg/l
Marine water 0,018 mg		0,018 mg/l
Freshwater sediment 1000 mg/		1000 mg/kg
Marine sediment 100 mg/kg		
Micro-organisms in sewage treatment plants (STP) 100 mg/l		
Soil		100 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection: Eye glasses with side protection goggles

Hand protection

Tested protective gloves must be worn: DIN EN 374 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 7 of 14

Thickness of the glove material >= 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste
Colour: blue

Odour: sweet odour

pH-Value: not applicable

Changes in the physical state

Melting point:
Initial boiling point and boiling range:

>200 °C

Flash point:

>93 °C

Flammability

Solid: not determined
Gas: not determined

Explosive properties

not explosive according to EU A.14

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not applicable

not applicable

Auto-ignition temperature

Solid: not determined
Gas: not determined

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 8 of 14

Vapour pressure: >1 (air=1) hPa

Density: 1,6 g/cm³

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water

Solubility in other solvents

No information available.

Partition coefficient: not determined

Viscosity / dynamic: 74k mPa·s

(at 25 °C)

Vapour density: not determined Evaporation rate: <1 (ether =1)

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Acid, Oxidising agent

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 9 of 14

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
25068-38-6	2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol					
	oral	LD50 mg/kg	> 2000	Rat	Study report (2007)	OECD Guideline 420
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2007)	OECD Guideline 402
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Print date: 12.01.2018



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 10 of 14

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
25068-38-6	2-(chloromethyl)oxirane;4	-[2-(4-hydro	oxyphenyl)pro	pan-2-yl]phenol		
	Acute fish toxicity	LC50	3,6 mg/l	96 h	Oncorhynchus mykiss	Study report (1982)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	Study report (2007)	OECD Guideline 201
	Acute crustacea toxicity	EC50	1,7 mg/l	48 h	Daphnia magna	Study report (1984)	OECD Guideline 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Study report (1984)	OECD Guideline 211
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol						
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1,8	72 h	Pseudokirchneriella subcapitata	Study report (1993)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Study report (1984)	OECD Guideline 211

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25068-38-6	2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol	>= 2,64
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2,7

BCF

CAS No	Chemical name	BCF	Species	Source
25068-38-6	2-(chloromethyl)oxirane;4-[2- (4-hydroxyphenyl)propan-2-yl]phenol	31		Study report (2010)
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	150		Other company data (

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 11 of 14

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Classification code:M6

Special Provisions: 274 335 375 601

Limited quantity:5 LExcepted quantity:E1Transport category:3Hazard No:90Tunnel restriction code:E

Inland waterways transport (ADN)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9Classification code:M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin

14.3. Transport hazard class(es):914.4. Packing group:III



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 12 of 14

Hazard label: 9
Marine pollutant: P

Special Provisions: 274, 335, 969

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9

Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A97 A158 A197

30 kg G

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

Danger releasing substance: epoxy resin

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 13 of 14

2-(chloromethyl)oxirane;4-[2-(4-hydroxyphenyl)propan-2-yl]phenol

Silicon carbide

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Titanium dioxide

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Further Information

This information is based solely on data privided by suppliers of the materials used, not on the mixture itself.

No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.

The user must make their own determination as to suitability.



according to Regulation (EC) No 1907/2006

ARC S2(E) Part A

Revision date: 12.01.2018 Page 14 of 14

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)