

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC 988(E) Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. Repair damage caused by impact, abrasion or erosion and chemical attack.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1A

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Harmful if swallowed.

Harmful in contact with skin.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 2 of 19

Hazard components for labelling

polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether
Amines, polyethylenepoly-, triethylenetetramine fraction
3,6-diazaoctanethylenediamin; triethylenetetramine
m-phenylenebis(methylamine)
Phenol, styrenated

Signal word: Danger

Pictograms:



Hazard statements

H302+H312	Harmful if swallowed or in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.

2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 3 of 19

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
	polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether	20 - < 25 %
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H317 H412	
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	15 - < 20 %
	292-588-2	01-2119487919-13
	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H314 H317 H412	
57214-10-5	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)	15 - < 20 %
	500-137-0	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
100-51-6	benzyl alcohol	15 - < 20 %
	202-859-9	603-057-00-5
	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319	
112-24-3	3,6-diazaoctanethylenediamin; triethylenetetramine	5 - < 10 %
	203-950-6	612-059-00-5
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412	
1477-55-0	m-phenylenebis(methylamine)	5 - < 10 %
	216-032-5	01-2119480150-50
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1, Skin Sens. 1, Aquatic Chronic 3; H332 H302 H314 H317 H412 EUH071	
61788-44-1	Phenol, styrenated	3 - < 7 %
	262-975-0	01-2119557886-19
	Skin Irrit. 2, Skin Sens. 1A, Aquatic Chronic 2; H315 H317 H411	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1 - < 5 %
	202-013-9	603-069-00-0
	01-2119560597-27	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319	
4097-89-6	N,N-Bis(2-aminoethyl)ethylendiamine	1 - < 5 %
	223-857-4	
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H310 H301 H314 H318 H412	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 4 of 19

General information

First aider: Pay attention to self-protection!

Take off immediately all contaminated clothing and wash it before reuse.

IF exposed or if you feel unwell: Immediately call a POISON CENTER or doctor/physician.

After inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.

Do not wash with: Solvents/Thinner

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

Harmful if swallowed.

Skin sensitisation

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 5 of 19

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.
Provide adequate ventilation.
Personal protection equipment: see section 8
Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8. Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8.
Wear personal protection equipment (refer to section 8).
Avoid breathing dust/fume/gas/mist/vapours/spray.
Avoid contact with skin, eyes and clothes.
Take off contaminated clothing and wash it before reuse.
Contaminated work clothing should not be allowed out of the workplace.
When using do not eat, drink or smoke.
Never use pressure to empty container. Keep/Store only in original container.
Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Further information on storage conditions

Keep away from:
Frost
Heat
Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 6 of 19

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction			
Worker DNEL, long-term		inhalation	systemic	1 mg/m ³
Worker DNEL, acute		inhalation	systemic	5380 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,57 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,29 mg/m ³
Consumer DNEL, acute		inhalation	systemic	1600 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,43 mg/cm ²
Consumer DNEL, acute		dermal	local	1 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,41 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day
57214-10-5	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)			
Worker DNEL, long-term		inhalation	systemic	0,02 mg/m ³
Worker DNEL, acute		inhalation	systemic	2 mg/m ³
Worker DNEL, long-term		inhalation	local	0,6 mg/m ³
Worker DNEL, acute		inhalation	local	6 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,385 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	3,85 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,0028 mg/cm ²
Worker DNEL, acute		dermal	local	0,0028 mg/cm ²
Consumer DNEL, long-term		dermal	systemic	0,00772 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	0,00772 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,000167 mg/cm ²
Consumer DNEL, acute		dermal	local	0,000167 mg/cm ²
Consumer DNEL, long-term		oral	systemic	3,33 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	3,33 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 7 of 19

100-51-6	benzyl alcohol		
Worker DNEL, long-term	inhalation	systemic	22 mg/m ³
Worker DNEL, acute	inhalation	systemic	110 mg/m ³
Worker DNEL, long-term	dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	5,4 mg/m ³
Consumer DNEL, acute	inhalation	systemic	27 mg/m ³
Consumer DNEL, long-term	dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	20 mg/kg bw/day
1477-55-0	m-phenylenebis(methylamine)		
Worker DNEL, long-term	dermal	systemic	0,33 mg/kg bw/day
Worker DNEL, long-term	inhalation	local	0,2 mg/m ³
Worker DNEL, long-term	inhalation	systemic	1,2 mg/m ³
61788-44-1	Phenol, styrenated		
Worker DNEL, long-term	inhalation	systemic	7,4 mg/m ³
Worker DNEL, long-term	dermal	systemic	2,1 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,31 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,75 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 8 of 19

PNEC values

CAS No	Substance	Value
Environmental compartment		Value
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	
Freshwater		0,19 mg/l
Freshwater (intermittent releases)		0,2 mg/l
Marine water		0,038 mg/l
Freshwater sediment		95,9 mg/kg
Marine sediment		19,2 mg/kg
Secondary poisoning		0,18 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,25 mg/l
Soil		19,1 mg/kg
57214-10-5	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)	
Freshwater		0,02 mg/l
Marine water		0,002 mg/l
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg
1477-55-0	m-phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine water		0,009 mg/l
Freshwater sediment		0,43 mg/kg
Marine sediment		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,045 mg/kg
61788-44-1	Phenol, styrenated	
Freshwater		0,03 mg/l
Freshwater (intermittent releases)		0,046 mg/l
Marine water		0,003 mg/l
Freshwater sediment		1,86 mg/kg
Marine sediment		0,186 mg/kg
Micro-organisms in sewage treatment plants (STP)		36,2 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 9 of 19

Soil	0,355 mg/kg
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
Freshwater	0,084 mg/l
Freshwater (intermittent releases)	0,84 mg/l
Marine water	0,008 mg/l
Micro-organisms in sewage treatment plants (STP)	0,2 mg/l

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection:

Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber), PVC (polyvinyl chloride)

Thickness of the glove material $\geq 0,4$ mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid, viscous
Colour: brown
Odour: like: Amines

Test method

pH-Value: not applicable

Changes in the physical state

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 10 of 19

Melting point: not applicable

Initial boiling point and boiling range: not applicable

Flash point: >93 °C

Flammability

Solid: No data available

Gas: No data available

Explosive properties

No information available.

Lower explosion limits: not applicable

Upper explosion limits: not applicable

Ignition temperature: No data available

Auto-ignition temperature

Solid: No data available

Gas: No data available

Decomposition temperature: No data available

Oxidizing properties

No information available.

Vapour pressure: No data available

Density: ~1,05 g/cm³

Water solubility: Immiscible

Solubility in other solvents

No information available.

Partition coefficient: No data available

Viscosity / dynamic:
(at 25 °C) ~350 mPa·s

Vapour density: >1 (air = 1)

Evaporation rate: <1 (Ether = 1)

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Does not decompose when used for intended uses. No known hazardous decomposition products.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 11 of 19

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Strong acid

Strong alkali

Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide, aldehydes, Acids

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Harmful in contact with skin.

ATEmix calculated

ATE (oral) 894,6 mg/kg; ATE (dermal) 1943,5 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 12 of 19

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether				
	oral	ATE 500 mg/kg			
	dermal	ATE 1100 mg/kg			
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction				
	oral	LD50 1861,9 mg/kg	Rat	Study report (1992)	other: EPA FR Vol.50, No. 188, September
	dermal	LD50 1465,4 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402
100-51-6	benzyl alcohol				
	oral	LD50 1580 mg/kg	Mouse	Cosmet. Toxicol. 11, 1011-1013 (1973) (1)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Raw Material Data Handbook, Vol.1:(Orga	EPA OTS 798.1100
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 >4,178 mg/l	Rat	ECHA	OECD 403
112-24-3	3,6-diazaoctanethylenediamin; triethylenetetramine				
	oral	LD50 2500 mg/kg	Rat		
	dermal	LD50 805 mg/kg	Rabbit		
1477-55-0	m-phenylenebis(methylamine)				
	oral	LD50 1180 mg/kg	Mouse	OECD Guideline 401	
	dermal	LD50 > 3100 mg/kg	Rabbit	TK 11813 was applied	
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 1,34 mg/l	Rat		
61788-44-1	Phenol, styrenated				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2014)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2014)	OECD Guideline 402
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol				
	oral	ATE 500 mg/kg			
4097-89-6	N,N-Bis(2-aminoethyl)ethylendiamine				

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 13 of 19

	oral	ATE	100			
		mg/kg				
	dermal	ATE	50 mg/kg			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether; Amines, polyethylenepoly-, triethylenetetramine fraction; 3,6-diazaoctanethylenediamin; triethylenetetramine; m-phenylenebis(methylamine); Phenol, styrenated)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 14 of 19

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction					
	Acute fish toxicity	LC50 330 mg/l	96 h	Pimephales promelas	Study report (1992)	other: U.S EPA-TSCA, 40 CFR Part 797.14
	Acute algae toxicity	ErC50 20 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1990)	OECD Guideline 201
	Acute crustacea toxicity	EC50 31,1 mg/l	48 h	Daphnia magna	Study report (1989)	EU Method C.2
	Acute bacteria toxicity	(800 mg/l)	0,5 h	activated sludge, domestic	Study report (1989)	other: EEC L133 1988 p 118-122
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 770 mg/l	72 h	Pseudokirchneriella subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Fish toxicity	NOEC 48,897 mg/l	30 d	Fish species	http://epa.gov/oppt/exposure/pubs/episui	other: QSAR
	Algae toxicity	NOEC 51 mg/l	3 d			
	Crustacea toxicity	NOEC 51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	(1385 mg/l)	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
112-24-3	3,6-diazaoctanethylenediamin; triethylenetetramine					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h			
	Acute crustacea toxicity	EC50 92 mg/l	48 h	Daphnia magna		
1477-55-0	m-phenylenebis(methylamine)					
	Acute fish toxicity	LC50 87,6 mg/l	96 h	Oryzias latipes (Ricefish)		
	Acute algae toxicity	ErC50 20,3 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 15,2 mg/l	48 h	Daphnia magna (Big water flea)		
	Algae toxicity	NOEC 10,5 mg/l	3 d	Selenastrum capricornutum		
	Crustacea toxicity	NOEC 4,7 mg/l	21 d	Daphnia magna (Big water flea)		
61788-44-1	Phenol, styrenated					

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 15 of 19

	Acute fish toxicity	LC50 mg/l	1,77	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	20,42	72 h	Chlorella vulgaris	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50	4,6 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC	1,9 mg/l	14 d	fish	REACH Registration Dossier	other: Refer below principle
	Crustacea toxicity	NOEC	0,2 mg/l	21 d	Daphnia magna	REACH Registration Dossier	other: Refer below principle
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol						
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio	Study report (1973)	other: Fish Bioassay Procedure in 1970 e

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-51-6	benzyl alcohol			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	95 - 97%	21	
	Readily biodegradable (according to OECD criteria).			
1477-55-0	m-phenylenebis(methylamine)			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	49 %	28	
	Not readily biodegradable (according to OECD criteria)			
61788-44-1	Phenol, styrenated			
	OECD 301F	7%	28	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	-2,65
100-51-6	benzyl alcohol	1
112-24-3	3,6-diazaoctanethylenediamin; triethylenetetramine	-1,66
1477-55-0	m-phenylenebis(methylamine)	0,18
61788-44-1	Phenol, styrenated	2,415
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	>= 0,219

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 16 of 19

BCF

CAS No	Chemical name	BCF	Species	Source
100-51-6	benzyl alcohol	1,371	QSAR model	http://epa.gov/oppt/
1477-55-0	m-phenylenebis(methylamine)	<0,3		
61788-44-1	Phenol, styrenated	18,21	fish	REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether, Amines, polyethylenepoly-, triethylenetetramine fraction)

14.3. Transport hazard class(es): 8

14.4. Packing group: III

Hazard label: 8

Classification code: C7

Special Provisions: 274

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 80

Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether, Amines, polyethylenepoly-, triethylenetetramine fraction)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 17 of 19

<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 2735
<u>14.2. UN proper shipping name:</u>	AMINES, LIQUID, CORROSIVE, N.O.S. (polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether, Amines, polyethylenepoly-, triethylenetetramine fraction)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Marine pollutant:	P
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B
Segregation group:	alkalis

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 2735
<u>14.2. UN proper shipping name:</u>	AMINES, LIQUID, CORROSIVE, N.O.S. (polymeric reaction product with triethylenetetramine and bisphenol-A-diglycidylether, Amines, polyethylenepoly-, triethylenetetramine fraction)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 18 of 19

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 3,6-diazaoctanethylenediamin; triethylenetetramine; 2,4,6-tris(dimethylaminomethyl)phenol

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Amines, polyethylenepoly-, triethylenetetramine fraction

benzyl alcohol

m-phenylenebis(methylamine)

Phenol, styrenated

2,4,6-tris(dimethylaminomethyl)phenol

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 988(E) Part B

Revision date: 11.07.2019

Page 19 of 19

LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1A; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H302+H312	Harmful if swallowed or in contact with skin.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself.
 No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.
 The user must make their own determination as to suitability.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)